



Easy to use, hard to beat: The 15MF400T delivers an integrated TV tuner, a fast response time for fine display detail, composite video and S-video options plus a great stereo sound system and even doubles as a high resolution PC monitor.

- Fast response time panel technology
- VGA input for use as a PC monitor
- Composite video and S-video inputs
- Stereo sound system





# 15MF400T/37 15" LCD TV

# **Product specifications**

# Picture/Display

- Aspect ratio: 4:3
- Brightness: 250 cd/m<sup>2</sup>
- Contrast ratio (typical): 400:1
- Display screen type: LCD XGA Active Matrix TFT
  Picture enhancement: 2D Combfilter, 3/2 2/2
- motion pull down, Black stretch, Progressive ScanScreen enhancement: Anti-Reflection coated
- screen
- Viewing angle (H / V): 120 / 100 degree
- Response time (typical): 16 ms
- Panel resolution: 1024 x 768p

# Supported Display Resolution

#### Resolution Refresh rate

| Computer formats |                  |
|------------------|------------------|
| 640 x 480        | 60, 72, 75Hz     |
| 800 x 600        | 56, 60, 72, 75Hz |
| 1024 x 768       | 60, 70, 75Hz     |
| Video formats    |                  |
| 480i             | 60Hz             |
| 480p             | 60Hz             |
|                  |                  |

#### Sound

- Output power (RMS): 2 speakers @ 2w each
- Sound Enhancement: Virtual Surround Sound
- Sound System: Mono, SAP

#### Convenience

- · Ease of Installation: Autostore, Fine Tuning
- Remote Control: TV
- Screen Format Adjustments: 4:3, 4:3 HD
- · Convenience Enhancements: Sleep Timer
- VESA Mount: 100 x 100 mm
- Child Protection: Child Lock+Parental Control

## **Tuner/Reception/Transmission**

- · Tuner bands: Hyperband, S-Channel, UHF, VHF
- TV system: NTSC
- Video Playback: Multi-system
- Aerial Input: 75 ohm F-type
- Number of channels (cable): 125
- Number of channels (off-air): 69

#### Connectivity

• AV 1: Audio L/R in, CVBS in

#### AV 2: S-Video

- Audio input for video: 1 x 3.5 mm phone jack
- PC: VGA-in D-Sub 15HD
- Rear Connections: Antenna F-type, Headphone out 3.5 mm jack

#### Power

- Power consumption: < 50 W
- Standby power consumption: < 2 W</li>
- Ambient temperature: 5 °C to 40 °C
- Mains power: 90-240 VAC, 50/60 Hz

#### **Dimensions**

- Product weight (+stand): 3.5 kg
- Product weight (+stand) (lb): 7.7 lb
- Set dimensions with stand (W x H x D): 371.6 x 346 x 147.5 mm
- Set dimensions with stand in inch (W x H x D): 14.6 x 13.6 x 5.8 inch

#### Accessories

 Included Accessories: Batteries for remote control, Power cord, Quick Use Guide, Remote Control, User Manual, Warranty certificate



# Fast response time

Faster response time delivers improved display of video action with faster transitions that dramatically reduce visible image artifacts in the display of fast-moving images.

# VGA input


VGA input provides a connector to accommodate input of an analog signal for use as a PC monitor.

# Composite and S-video inputs

A variety of format choices in connecting video devices.

### Stereo sound system

A system that receives stereo broadcasts for high power performance with exciting and lifelike sound through dual speakers.



Date of issue 2008-04-04

Version: 3.0.8

12 NC: 8639 000 16595 UPC: 0 37849 96552 8 Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their

© 2008 Magnavox.
 All Rights reserved.

www.magnavox.com